

RIG 10 EDSON 3000G SPECIFICATIONS

EDSON 3000G



Name, Model No & Type:	Edson 3000G	Max Practical Depth, HQ (m):	220m
Owner:	J&S Drilling	Max Practical Depth, PQ (m):	180m
Build date:	2013	Height Overall, mast down (m):	4.3m
Gross Registered Tonnage	15 tonne	Height Overall, mast up (m):	9m
(state type):			
Maximum Power (kW):	132@2500rpm	Maximum Torque (Nm):	8000
Length Overall (m):	8.97m	Useable Fuel Capacity (L):	300L
Width Overall (m):	2.5m	Maximum Feed Force (kN):	83
Maximum Pump Pressure:	3600psi	Maximum Stroke (m):	3.8
Main Pump Flow (L/min):	185	Maximum Rod Pull (m):	7m
Main Pump:	FMC	Recirculating Pump:	Stalker
	W1122BCD	_	50HL
Recirculating Pump Flow	140 Variable	Other (specify):	
(L/min):			

125mm Mud Rotary	250mm Mud Rotary	75mm Auger	75mm Auger Coring	100mm Auger Coring	PQ3	HQ3	NQ3	Air Core	Air Drilling
175m	110m	75m	75m	55m	180m	220m	300m	60m	175m

DRILL RIG 10.doc Page 1 of 2



RIG 10 EDSON 3000G SPECIFICATIONS

Rod Breakout Setup



Rig 10 and Mud Puppy setup

DRILL RIG 10.doc Page 2 of 2