

## RIG 7 EDSON 3000G SPECIFICATIONS



Make/ Model:	EDSON 3000G	Max Practical Depth, HQ (m):	220m
Owner:	J&S Drilling	Max Practical Depth, PQ (m):	180m
Maximum Power (kW):	132 @ 2500RPM	Height Overall, mast down (m):	3.9m
Gross Registered Tonnage (state type):	15 tonnes	Height Overall, mast up (m):	8.9m
Length Overall (m):	8.5m	Maximum Torque (Nm):	8000
Width Overall (m):	2.5m	Useable Fuel Capacity (L):	180L
Rod Make & Break	Auto	Maximum Feed Force (kN):	80
Main Pump Flow(L/min):	180	Maximum Stroke (m):	3.6
Main Pump:	FMC W1122BCD	Maximum Rod Pull (m):	7m
Maximum Hydraulic Pump Pressure:	4600psi		
Recirculating Pump (L/min):	3300L/m 180psi	Recirculating Pump:	Mission Magnum

*Specifications are subject to change and inspections to satisfy intended use is recommended*

125mm Mud Rotary	250mm Mud Rotary	75mm Auger	75mm Auger Coring	100mm Auger Coring	PQ3	HQ3	NQ3	Air Core	Air Drilling
175m	110m	75m	75m	55m	180m	220m	300m	60m	175m